

Epoxy Insulated Load Breaker Switch (Underground line)

RS□L series

▶ EPOXY INSULATED LOAD BREAKER SWITCH_UNDERGROUND LINE

Epoxy Insulated multiway Load Breaker Switch for underground line.
(Eco-friendly products with no greenhouse gas emissions)



▶ FEATURE



▶ HIGH RELIABILITY

- Simple operating mechanism
- Switchgear vessel made of stainless steel
- Climate-independent
- Easy installation and operation

▶ SPECIFICATIONS

ITEM	RS1L	RS2L
Rated voltage (kV)	15	24
Rated normal current (A)	630	
Rated normal frequency (Hz)	50 / 60	
Rated lightning impulse withstand voltage (kV)	95 / 110	125 / 145
Rated power-frequency withstand voltage (kV)	36 / 40	50 / 60
Rated short-time withstand current (kA)	12.5 / 16	
Rated duration of short circuit(RMS) (kA)	12.5 / 16	
Rated short-circuit making current(Peak) (kA)	32.5 / 41.6	
Mechanical endurance (Operating Cycles)	Min. 5000	
Rated mainly active load breaking current	630	
Rated cable-charging breaking current	25	
Rated line-charging breaking current	1.5	
Applied Standard	IEC 62271-103	